Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LED-Strahler Plug & Light

Supplier's address: Albrecht JUNG GmbH & Co. KG, Zentrale, Volmestraße 1, 58579 Schalksmühle,

DE

Model identifier: PLS1D05SWSW

Type of light source:	Type	of light	source:
-----------------------	------	----------	---------

Lighting technology used:	LED	Non-directional or directional:	DLS	
Light source cap-type	Nein			
(or other electric interface)				
Mains or non-mains:	NMLS	Connected light source (CLS):	Nein	
Colour-tuneable light source:	Nein	Envelope:	-	
High luminance light source:	Nein			
Anti-glare shield:	Nein	Dimmable:	Only with specific dimmers	
Due de est recursos de un				

Product parameters

Parameter	Value	Parameter	Value			
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	6	Energy efficiency class	G			
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	390 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	26002700			
On-mode power (P _{on}), expressed in W	5,3	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,04			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	_	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82			

_					
Outer	Height	88	Spectral power	See image	
dimensions	Width	42	distribution in the	in last page	
without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	42	range 250 nm to 800 nm, at full-load		
Claim of equiva	lent power ^(a)	-	If yes, equivalent power (W)	-	
			Chromaticity	0,462	
			coordinates (x and y)	0,404	
Parameters for	directional light	sources:			
Peak luminous i	ntensity (cd)	750	Beam angle in degrees, or the range of beam angles that can be set	41	
Parameters for LED and OLED light sources:					
R9 colour rende	ering index value	8	Survival factor	0,99	
the lumen main	tenance factor	0,96			
L					

(a)'-': not applicable; (b)'-': not applicable;

